

| MODELO | EQUIVAL- ENTE | VOLT | AMP- HRS | No. DE PLACAS | Polaridad | Caract. Específicas | DIMENSIONES(mm) | | |
|--------|------------------|------|-------------|------------------|-----------|------------------------|-----------------|-------|------|
| | | | | | | | LARGO | ANCHO | ALTO |

BATERIAS CONVENCIONALES YUASA

| | | | | | | | | | |
|----------|----------|----|-----|----|-----|------------|-----|-----|-----|
| NS40ZL | NS40ZL | 12 | 45 | 9 | -/+ | POSTE DELG | 197 | 127 | 225 |
| NS60LS | N40L | 12 | 55 | 9 | -/+ | POSTE STD | 237 | 127 | 225 |
| NS60L | | 12 | 55 | 9 | -/+ | POSTE DELG | 237 | 127 | 224 |
| N50Z | 24/2SM | 12 | 75 | 11 | +/- | POSTE STD | 258 | 170 | 225 |
| NS70L | NX110-5L | 12 | 85 | 13 | -/+ | POSTE STD | 258 | 170 | 225 |
| N70Z | 27/3SM | 12 | 90 | 13 | +/- | POSTE STD | 300 | 170 | 225 |
| NX120-7L | NX120 I | 12 | 100 | 15 | -/+ | POSTE STD | 297 | 171 | 225 |
| N120 | 2D | 12 | 120 | 21 | +/- | EN SECO | 505 | 184 | 201 |
| N150 | 4D | 12 | 170 | 25 | +/- | POSTE STD | 508 | 223 | 236 |
| N200 | 8D | 12 | 220 | 31 | +/- | POSTE STD | 513 | 273 | 264 |
| DIN 88 | 58815 | 12 | 90 | 15 | -/+ | BAJA | 352 | 175 | 190 |

BATERIAS CONVENCIONALES

| | | | | | | | | | |
|-----------|------------|----|-----|----|-----|-----------|-----|-----|-----|
| N40 | 51 | 12 | 55 | 9 | +/- | POSTE STD | 237 | 127 | 225 |
| N40L | 51R | 12 | 55 | 9 | -/+ | POSTE STD | 237 | 127 | 225 |
| 26R | 26R | 12 | 60 | 9 | -/+ | POSTE STD | 207 | 172 | 198 |
| 26 | 22F | 12 | 60 | 9 | +/- | POSTE STD | 247 | 169 | 205 |
| N50Z | 24/2SM | 12 | 75 | 11 | +/- | POSTE STD | 258 | 170 | 225 |
| N50ZL | 24F | 12 | 75 | 11 | -/+ | POSTE STD | 258 | 170 | 225 |
| NS70 | NX110-5 | 12 | 85 | 13 | +/- | POSTE STD | 258 | 170 | 225 |
| NS70L | NX110-5L | 12 | 85 | 13 | -/+ | POSTE STD | 258 | 170 | 225 |
| N70Z | 27/3SM | 12 | 90 | 13 | +/- | POSTE STD | 300 | 170 | 225 |
| N70ZL | 27F | 12 | 90 | 13 | -/+ | POSTE STD | 300 | 170 | 225 |
| NX120-7 | NX120 | 12 | 100 | 15 | +/- | POSTE STD | 297 | 171 | 225 |
| NX120-7L | NX120 I | 12 | 100 | 15 | -/+ | POSTE STD | 297 | 171 | 225 |
| 31P | 30H | 12 | 105 | 17 | +/- | POSTE | 343 | 173 | 235 |
| 31S | 31T | 12 | 105 | 17 | +/- | PERNO | 343 | 173 | 235 |
| DIN 55 | 42L/42P | 12 | 65 | 11 | -/+ | BAJA | 246 | 175 | 190 |
| DIN 55R | 42LH/42P I | 12 | 65 | 11 | +/- | BAJA | 246 | 175 | 190 |
| DIN 66-41 | 41P/65 | 12 | 80 | 13 | -/+ | BAJA | 292 | 175 | 177 |
| DIN 66-48 | 48 | 12 | 90 | 15 | -/+ | BAJA | 278 | 175 | 190 |
| 4DLT | 4DLT | 12 | 150 | 23 | -/+ | POSTE STD | 508 | 208 | 207 |
| N150 | 4D | 12 | 170 | 25 | +/- | POSTE STD | 508 | 223 | 236 |
| N200 | 8D | 12 | 220 | 31 | +/- | POSTE STD | 513 | 273 | 264 |

BATERIAS SELLADAS DE LIBRE MANTENIMIENTO

| | | | | | | | | | |
|-----------|-----------|----|----|----|-----|-----------|-----|-----|-----|
| NS40ZL MF | NS40ZL MF | 12 | 45 | 9 | -/+ | SELLADA | 196 | 139 | 222 |
| N40L MF | 51 MF | 12 | 55 | 9 | -/+ | SELLADA | 238 | 127 | 222 |
| 26R-99 MF | 99 MF | 12 | 60 | 9 | -/+ | SELLADA | 207 | 175 | 174 |
| 26R MF | 26R MF | 12 | 60 | 9 | -/+ | SELLADA | 207 | 172 | 198 |
| N50Z MF | 24R MF | 12 | 75 | 11 | +/- | SELLADA | 278 | 172 | 227 |
| N50ZL MF | 24 MF | 12 | 75 | 11 | -/+ | SELLADA | 278 | 172 | 227 |
| NS70L MF | NX110-5L | 12 | 85 | 13 | -/+ | POSTE STD | 258 | 170 | 225 |
| DIN55 MF | 42 MF | 12 | 65 | 11 | -/+ | BAJA | 240 | 175 | 174 |

| | | | | | | | | | |
|------------|--------|----|----|----|-----|-------------|-----|-----|-----|
| DIN55R MF | 42R MF | 12 | 65 | 11 | +/- | BAJA | 240 | 175 | 174 |
| 35 MF | 35 MF | 12 | 75 | 11 | -/+ | SELLADA | 229 | 170 | 223 |
| 65 MF | 65 MF | 12 | 85 | 13 | +/- | SELLADA | 290 | 183 | 167 |
| 75DT MF | | 12 | 65 | 11 | +/- | LATERAL OJO | 230 | 164 | 186 |
| 78DT MF | 34-600 | 12 | 85 | 13 | +/- | POSTE STD | 260 | 180 | 186 |
| 34/78DT MF | 34-800 | 12 | 85 | 13 | +/- | LATERAL OJO | 260 | 187 | 205 |